















SPECIFICATIONS

	GEOLOGY	Mica-Schist Quartz (Quartzitic Sandstone)
	TYPE	
	PATTERN	2:1 or 2:3, Sawn Course Heights Dimensional Tight-fit
	HEIGHTS	1" - 2" (~50%), 3" (~25%), 5" (~25%)
	LENGTHS	4" - 14"
	DEPTHS	3/4" to 1-1/4"
	COLORS	Gray-Grey , Silver
	COVERAGE	Available in thin veneer only.
	WEIGHT	12.7 lbs. per square foot
	FLATS	5 s/f Bag, 10 s/f Box, 90/150/180 s/f Crate
	CORNERS	5 l/f Bag, 10 l/f Box, 90/100 l/f Crate
	NOTES	Packaged assuming a tight-fit installation comprising of 50% Silver Ledgestone , 50% sawn-height jumpers. Please review the Corners Installation PDF document.

ASTM C-97

Water Absorption %	.31 psi
Bulk Specific Gravity	2.83 psi

ASTM C-170

Parallel to Rift, Dry	36100 psi
Parallel to Rift, Wet	32000 psi
Perpendicular to Rift, Dry	35800 psi
Perpendicular to Rift, Wet	30000 psi

ASTM C-99

Parallel to Rift, Dry	3770 psi
Parallel to Rift, Wet	3500 psi

ASTM C-880

Perpendicular to Rift, Dry	1780 psi
Perpendicular to Rift, Wet	1730 psi



GOLD QUARRY
 ANSI/NSC 373-2013
 C0290908-101



GOLD FABRICATOR
 ANSI/NSC 373-2013
 C0289215-101