















SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	Tumbled, 100% Bedface
	PATTERN	Mosaic
	HEIGHTS	Irregular shaped up to 16" across
	LENGTHS	Up to 16" across
	DEPTHS	3/4" - 1 1/4" (Thin Veneer); 3"-5" Full Veneer)
	COLORS	Beige, Buff, Tan hues with soft, aged appearance.
	COVERAGE	35-40 sq ft per ton (full bed-depth)
	WEIGHT	13.7 lbs. per square foot (Thin Veneer)
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	10 l/f Box; 100 l/f Crate; 100 l/f pallet
	NOTES	

ASTM C-97

Water Absorption %	.50 psi
Bulk Specific Gravity	2.79 psi

ASTM C-170

Parallel to Rift, Dry	21300 psi
Parallel to Rift, Wet	20300 psi
Perpendicular to Rift, Dry	29400 psi
Perpendicular to Rift, Wet	29100 psi

ASTM C-99

Parallel to Rift, Dry	2040 psi
Parallel to Rift, Wet	1690 psi

ASTM C-880

Perpendicular to Rift, Dry
Perpendicular to Rift, Wet



GOLD QUARRIER
 ANSI/NSC 373-2013
 C0290908-101



GOLD FABRICATOR
 ANSI/NSC 373-2013
 C0289215-101