















SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	100% Bedface
	PATTERN	Mosaic
	HEIGHTS	Irregular shaped stone up to 16" across
	LENGTHS	Up to 16" across (Full Bed & Thin Veneer)
	DEPTHS	3/4" to 1-1/4" (Thin Veneer)
	COLORS	Beige, Brown, Buff, Tan
	COVERAGE	Full Bed Depth Veneer: 30-40 Square Feet Per Ton
	WEIGHT	13.4 lbs. per square foot.
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	10 l/f Box; 100 l/f Crate; 100 l/f pallet
	NOTES	Heritage Mosaic™ is/was also known as the legacy NSVI product, "Bridgewater". Some photos may still use the former product name.

ASTM C-97

Water Absorption %	1.60 psi
Bulk Specific Gravity	2.54 psi

ASTM C-170

Parallel to Rift, Dry	15100 psi
Parallel to Rift, Wet	13200 psi
Perpendicular to Rift, Dry	15100 psi
Perpendicular to Rift, Wet	14400 psi

ASTM C-99

Parallel to Rift, Dry	1110 psi
Parallel to Rift, Wet	1110 psi

ASTM C-880

Perpendicular to Rift, Dry	1780 psi
Perpendicular to Rift, Wet	2060 psi



GOLD QUARRY
 ANSI/NSC 373-2013
 C0290908-101



GOLD FABRICATOR
 ANSI/NSC 373-2013
 C0289215-101