















## SPECIFICATIONS

	<b>GEOLOGY</b>	Mica-Schist Quartz (quartzitic sandstone)
	<b>TYPE</b>	
	<b>PATTERN</b>	2:1 or 2:3, Sawn Course Heights   Dimensional or Ashlar   Tight-fit
	<b>HEIGHTS</b>	1" - 2" (~50%); 3" (~25%), 5" (~25%)
	<b>LENGTHS</b>	4"-14"
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Buff, Brown hues, Bronze, Copper, Gray-Grey, Silver
	<b>COVERAGE</b>	Available in thin veneer only.
	<b>WEIGHT</b>	12.7 lbs per square foot
	<b>FLATS</b>	5 s/f Bag, 10 s/f Box, 90/150/180 s/f Crate
	<b>CORNERS</b>	5 l/f Bag, 10 l/f Box, 90/100 l/f crate
	<b>NOTES</b>	<b>Packaged assuming a tight-fit installation comprising of 50% Virginia Ledgestone, 50% sawn-height jumpers.   Please review the Corners Installation PDF document.</b>

### ASTM C-97

Water Absorption %	.9 psi
Bulk Specific Gravity	

### ASTM C-170

Parallel to Rift, Dry	18175 psi
Parallel to Rift, Wet	31470 psi
Perpendicular to Rift, Dry	
Perpendicular to Rift, Wet	

### ASTM C-99

Parallel to Rift, Dry	5584 psi
Parallel to Rift, Wet	5502 psi

### ASTM C-880

Perpendicular to Rift, Dry	3984 psi
Perpendicular to Rift, Wet	1064 psi



**GOLD QUARRY**  
 ANSI/NSC 373-2013  
 C0290908-101



**GOLD FABRICATOR**  
 ANSI/NSC 373-2013  
 C0289215-101