















SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	70% Split-face (Indigo Country™), 30% Bed-face (Indigo Manor™)
	PATTERN	Natural Course Heights 2:1 Random Ashlar
	HEIGHTS	2" - 9" (Full Bed); 2"-9" (Thin Veneer)
	LENGTHS	Random, 8" - 36" (Full Bed); 8"-24" (Thin Veneer, crated/palletized material can exceed 20")
	DEPTHS	3/4" - 1 1/4" (Thin Veneer); 3" - 5" Full bed-depth
	COLORS	Grays, blue hues, some buff
	COVERAGE	Full Bed Depth Veneer: 35-40 Square Feet Per Ton. Also Available in Thin Veneer.
	WEIGHT	14 pounds per square foot (thin veneer)
	FLATS	Thin Veneer: 10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet
	CORNERS	Thin Veneer: 10 l/f Box; 100 l/f Crate; 100 l/f pallet
	NOTES	Pre-packaged 70% Split-face (Indigo Country™), 30% Bed-face (Indigo Manor™)

ASTM C-97

Water Absorption %	.50 psi
Bulk Specific Gravity	2.79 psi

ASTM C-170

Parallel to Rift, Dry	21300 psi
Parallel to Rift, Wet	20300 psi
Perpendicular to Rift, Dry	29400 psi
Perpendicular to Rift, Wet	29100 psi

ASTM C-99

Parallel to Rift, Dry	2040 psi
Parallel to Rift, Wet	1690 psi

ASTM C-880

Perpendicular to Rift, Dry	
Perpendicular to Rift, Wet	



